

# Gunite Optimum Lightweight Drum

## Gunite GOLD<sup>®</sup> Quick Reference Guide

LIGHTWEIGHT | LONGER LIFE | LESS NOISE

DURABLE | FLEET TESTED | PROVEN PERFORMANCE



Made in the USA



Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS



# Gunite Optimum Lightweight Drum

## Gunite GOLD® Quick Reference Guide

### DIMENSIONAL LISTING

Brake Size	Gunite GOLD® P/N	Overall Depth	Width of Brake Surface	Pilot Diam.	Bolt Circle Diam.	Bolt Holes		Wheel Type	Drum Mount <sup>(1)</sup>	Drum Weight	Special Information
						No.	Size				
15.00 x 4.00	9035X	8.40	4.58	8.78	11.25	10	1.25	Disc	0	64 lbs	Lightweight version of 3596X Mack only
15.00 x 4.00	9000X	8.60	4.78	8.78	11.25	10	1.25	Disc	0	66 lbs	Lightweight version of 3721AX
15.00 x 4.00	9001X	8.99	4.66	8.78	11.25	10	1.25	Disc	0	69 lbs	Lightweight version of 3800X
15.00 x 4.00	9016X	8.99	4.66	9.00	275mm	8	1.00	Disc	0	70 lbs	Lightweight version of 3741X
16.50 x 5.00	9002X	8.85	5.38	8.78	11.25	10	1.25	Disc	0	80 lbs	Lightweight version of 3710X
16.50 x 5.00	9003X	9.23	5.48	8.78	11.25	10	1.25	Disc	0	79 lbs	Lightweight version of 3598X and 3758X
16.50 x 7.00	9015X	8.80	7.50	9.50	11.25	10	0.81	Disc/Spoke	I	89 lbs	Lightweight version of 3018AX
16.50 x 7.00	9014X	9.56	7.56	9.44	11.25	10	0.84	Disc	I	90 lbs	Lightweight version of 2705X
16.50 x 7.00	9022X	10.10	7.34	8.53	11.25	10	0.81	Disc	0	94 lbs	Lightweight version of 3699X
16.50 x 7.00	9036X	10.11	7.40	8.78	11.25	10	1.00	Disc	0	98 lbs	Lightweight version of 3402X
16.50 x 7.00	9006X	10.34	7.66	8.78	11.25	10	1.00	Disc	0	94 lbs	Lightweight version of 3600AX
16.50 x 7.00	9021X	10.46	7.70	8.53	11.25	10	1.00	Disc	0	96 lbs	Lightweight version of 3483X
16.50 x 7.00	9041BX	10.50	7.85	9.00	275mm	8	1.00	Disc	0	99 lbs	Lightweight version of 3141BX
16.50 x 7.00	9041X	10.50	7.85	9.00	11.25	10	1.00	Disc	0	99 lbs	Lightweight version of 3141X
16.50 x 8.00	9020X	10.78	8.66	8.78	11.25	10	1.00	Disc	0	105 lbs	Lightweight version of 3782X
16.50 x 8.62	9019X	11.12	9.00	8.78	11.25	10	1.00	Disc	0	107 lbs	Lightweight version of 3807X

### PART NUMBER CROSS REFERENCE

Gunite GOLD® P/N	Standard Gunite Drum	Meritor X-30™	Stemco Motor Wheel CentriFuse®	Webb Standard Cast Drum
9000X	3721AX	53-123512-002	90089BK	n/a
9001X	3800X	53-123542-002	89870BK	69870B
9002X	3710X	53-123606-002	90137B	n/a
9003X	3758X	53-123589-002	90600B	65151B
9006X	3600AX	53-123537-002	89996B	69996B
9014X	2705X	53-123585-002	87407B	67407B
9015X	9018AX	n/a	87415B	n/a
9016X	3741X	53-123575-002	88870BK	n/a
9019X	3807X	53-123581-002	90486B	66854B
9020X	3782X	53-123535-002	91792B	66800B
9021X	3483X	53-123564-002	87101B	67101B
9022X	3699X	53-123582-002	87295B	n/a
9035X <sup>(2)</sup>	3596AX	53-123512-002	90089BK	n/a
9036X	3402X	53-123583-002	89877B	n/a
9041X	3141X	53-123565-002	87156B	68797B
9041BX	3141BX	53-123566-002	88797B	66800B

<sup>(1)</sup>(O) Drum mounts on the outboard face of the disc wheel hub.

<sup>(I)</sup> Drum mounts on the inboard face of the disc wheel hub.

<sup>(2)</sup>Mack applications only.

### Note:

Gunite GOLD® drive and trailer axle drums are approved for applications through 23,000 lbs. single axle GAWR (46,000 lbs. tandem axle GAWR).

Gunite GOLD® 15.00x4.00 steer axle drums are approved for applications through 14,600 lbs. GAWR.

When utilizing Gunite GOLD® lightweight brake drums in lieu of standard brake drums, it may be necessary to replace the disc wheel bolts in order to achieve the proper stud standout. Reference Gunite GOLD® Disc Wheel Hub Application Guide, GUN2.0003, for additional information on GOLD® Drum/Hub/Stud Interchanges.



**Made in the USA**

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS

For more information: (800) 677-3786 | (815) 964-3301 | [accuridewheelendsolutions.com](http://accuridewheelendsolutions.com)

Gunite | 302 Peoples Avenue | Rockford, IL 61104-7092

