

Gunite® Automatic Slack Adjusters

Proven technology from a brand you can trust



Assembled in the USA



Your only single source for industry-leading wheel end solutions.
STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS



Gunite® Automatic Slack Adjusters

Gunite Quality Slack Adjusters

Gunite Slack Adjusters are proven, year after year, as the standard of the industry in providing superior performance, reduced maintenance costs and consistent, long-term reliability, trip after trip. You can depend on Gunite quality.

WHY CHOOSE GUNITE AUTOMATIC SLACK ADJUSTERS?

Features	Benefits
Sensing Type	Gunite's unique clearance sensing design adjusts on the apply stroke, accurately reading the shoe-to-drum clearance when the brake drums are coolest and deflection of the brake system components are minimal.
Clutch	Gunite utilizes a 90-tooth Cone Clutch that provides fine incremental adjustments to ensure proper shoe-to-drum clearance.
Clutch Spring	Gunite's use of Belleville Springs provides a clutch preload that does not fade over time.
Adjustment Occurs	Gunite's Automatic Slack Adjuster adjusts on the applied stroke, and as such does not react to drum growth encountered during any single brake application. Operation is not dependent on the air chamber return spring and brake shoe return spring condition.
Drilled Worm Gear	All Gunite Automatic Slack Adjusters have a drilled worm gear for lubrication to help prevent seizure of the S-Cam splines under extreme conditions.
Gear Teeth	Gunite's use of a Worm Gear Buttress Teeth Design Set provides greater loading capability, fatigue life, enhanced durability, and higher S-Cam torque.
Threaded and Welded on Clevis Applications	Gunite Automatic Slack Adjusters are available for air brake chambers that have a threaded push rod and push rods with welded on clevis.
Warranty	Industry leading coverage.

TOP 12 PART NUMBERS

Gunite P/N	Packaged Weight (lbs.)	Arm Length	Number of Splines	Spline Diameter	Clevis Included	Application
AS1140	8.0	5.5"	28	1.50"	AS3019	All Positions
AS1141	8.0	6.0"	28	1.50"	AS3016	Drive
AS1132	8.0	5.5"	10	1.50"	AS3019	All Positions
AS1133	8.0	6.0"	10	1.50"	AS3016	Drive
AS1136	8.0	5.5"	10	1.25"	AS3019	Front, Dolly
AS1149	8.0	5.5"	28	1.50"	AS3018	Trailer
AS1150	8.0	6.0"	28	1.50"	AS3018	Trailer
AS1138	8.0	5.5"	24	1.25"	AS3019	Front, Dolly
AS1144	8.0	6.0"	37	1.50"	AS3018	Trailer
AS1147	8.0	6.0"	10	1.50"	AS3018	Trailer
AS1172 ⁽¹⁾	8.0	5.5"	28	1.50"	None	All Positions
AS1173 ⁽¹⁾	8.0	6.0"	28	1.50"	None	All Positions



Assembled in the USA



Consult the Gunite Automatic Slack Adjuster parts catalog for Clevis Kit descriptions and Interchange information.

(1) Gunite 2000 - for welded on clevis applications

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS

For more information: (800) 677-3786 / (815) 964-3301 | accuridewheelendsolutions.com

Gunite | 302 Peoples Avenue | Rockford, IL 61104-7092



ACCURIDE
WHEEL END SOLUTIONS

