



Gunite Automatic Slack Adjusters



Assembled in the USA

Proven technology from a brand you can trust

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS



Automatic Slack Adjuster

Gunite Automatic Slack Adjusters are proven year after year as the industry standard for superior performance, reduced maintenance costs, and consistent long-term reliability. You can count on Gunite quality to get you there safely.

WHY CHOOSE GUNITE AUTOMATIC SLACK ADJUSTERS?

| Features | Benefits |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sensing Style Adjustment | Gunite's unique clearance sensing design accurately senses shoe-to-drum clearance when brake drums are coolest and deflection of the brake components is minimal, ensuring optimal shoe adjustment. |
| 90-Tooth Cone Clutch | Gunite's cone clutch design provides fine incremental adjustments to ensure proper shoe-to-drum clearance. |
| Belleville Clutch Spring | Eliminates clutch fade over time to maintain consistent preload and performance. |
| Application Stroke Adjustment | Gunite's Automatic Slack Adjuster adjusts on the brake application stroke and is not affected by drum growth encountered during any single brake application. Operation is not dependent on the air chamber return spring and brake shoe return spring condition. |
| Drilled Worm Gear | Gunite's drilled worm gear enables lubrication to the S-Cam splines to prevent seizing under extreme conditions. |
| Buttress-Style Worm Gear Teeth | Strong tooth design to provide greater loading capability, fatigue life, enhanced durability, and higher S-Cam torque for more powerful brake applications. |
| Threaded or Welded On Clevis Applications | More application coverage for air brake chambers that have a threaded push rod or push rod with welded on clevis. |
| SLIC Pin Clevis Attachment | Easy to use spring loaded locking pin that eliminates the need for a cotter pin, simplifying installation and maintenance. |
| Industry Leading Warranty Coverage | For your peace of mind because Gunite stands behind their Automatic Slack Adjusters so you can focus on getting there safely. |

TOP 12 PART NUMBERS

| Gunite P/N | Packaged Weight (lbs.) | Arm Length | Number of Splines | Spline Diameter | Clevis Included | Application |
|-----------------------|------------------------|------------|-------------------|-----------------|-----------------|---------------|
| AS1140 | 8.0 | 5.5" | 28 | 1.50" | AS3019 | All Positions |
| AS1141 | 8.0 | 6.0" | 28 | 1.50" | AS3016 | Drive |
| AS1132 | 8.0 | 5.5" | 10 | 1.50" | AS3019 | All Positions |
| AS1133 | 8.0 | 6.0" | 10 | 1.50" | AS3016 | Drive |
| AS1136 | 8.0 | 5.5" | 10 | 1.25" | AS3019 | Front, Dolly |
| AS1149 | 8.0 | 5.5" | 28 | 1.50" | AS3018 | Trailer |
| AS1150 | 8.0 | 6.0" | 28 | 1.50" | AS3018 | Trailer |
| AS1138 | 8.0 | 5.5" | 24 | 1.25" | AS3019 | Front, Dolly |
| AS1144 | 8.0 | 6.0" | 37 | 1.50" | AS3018 | Trailer |
| AS1147 | 8.0 | 6.0" | 10 | 1.50" | AS3018 | Trailer |
| AS1172 ⁽¹⁾ | 8.0 | 5.5" | 28 | 1.50" | None | All Positions |
| AS1173 ⁽¹⁾ | 8.0 | 6.0" | 28 | 1.50" | None | All Positions |



Assembled in the USA



Consult the Gunite Automatic Slack Adjuster parts catalog for Clevis Kit descriptions and Interchange information.

(1) Gunite 2000 - for welded on clevis applications

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS

For more information: (800) 823-8332 | accuridecorp.com

Accuride | 7140 Office Circle | Evansville, IN 47715 USA



ACCURIDE
WHEEL END SOLUTIONS

