



## Gunite Automatic Slack Adjusters



Assembled in the USA

Proven technology from a brand you can trust

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS



## Automatic Slack Adjuster

Gunite Automatic Slack Adjusters are proven year after year as the industry standard for superior performance, reduced maintenance costs, and consistent long-term reliability. You can count on Gunite quality to get you there safely.

### WHY CHOOSE GUNITE AUTOMATIC SLACK ADJUSTERS?

Features	Benefits
Sensing Type	Gunite's unique clearance sensing design adjusts on the apply stroke, accurately reading the shoe-to-drum clearance when the brake drums are coolest and deflection of the brake system components are minimal.
Clutch	Gunite utilizes a 90-tooth Cone Clutch that provides fine incremental adjustments to ensure proper shoe-to-drum clearance.
Clutch Spring	Gunite's use of Belleville Springs provides a clutch preload that does not fade over time.
Adjustment Occurs	Gunite's Automatic Slack Adjuster adjusts on the applied stroke, and as such does not react to drum growth encountered during any single brake application. Operation is not dependent on the air chamber return spring and brake shoe return spring condition.
Drilled Worm Gear	All Gunite Automatic Slack Adjusters have a drilled worm gear for lubrication to help prevent seizure of the S-Cam splines under extreme conditions.
Gear Teeth	Gunite's use of a Worm Gear Buttress Thread Design Set provides greater loading capability, fatigue life, enhanced durability, and higher S-Cam torque.
Non-Handed	Gunite Automatic Slack Adjusters are non-handed, requiring fewer part numbers to order and inventory.
External Attachments	Gunite Automatic Slack Adjusters do not require external mounting brackets.
Industry-Best Warranty	Gunite offers extended mileage with 6-years/1 million miles warranty

### TOP 12 PART NUMBERS

Gunite P/N	Packaged Weight (lbs.)	Arm Length	Number of Splines	Spline Diameter	Clevis Included	Application
AS1140	8.0	5.5"	28	1.50"	AS3019	All Positions
AS1141	8.0	6.0"	28	1.50"	AS3016	Drive
AS1132	8.0	5.5"	10	1.50"	AS3019	All Positions
AS1133	8.0	6.0"	10	1.50"	AS3016	Drive
AS1136	8.0	5.5"	10	1.25"	AS3019	Front, Dolly
AS1149	8.0	5.5"	28	1.50"	AS3018	Trailer
AS1150	8.0	6.0"	28	1.50"	AS3018	Trailer
AS1138	8.0	5.5"	24	1.25"	AS3019	Front, Dolly
AS1144	8.0	6.0"	37	1.50"	AS3018	Trailer
AS1147	8.0	6.0"	10	1.50"	AS3018	Trailer
AS1172 <sup>(1)</sup>	8.0	5.5"	28	1.50"	None	All Positions
AS1173 <sup>(1)</sup>	8.0	6.0"	28	1.50"	None	All Positions



Assembled in the USA

Consult the Gunite Automatic Slack Adjuster parts catalog for Clevis Kit descriptions and Interchange information.

(1) Gunite 2000 - for welded on clevis applications

Scan this code to search Automatic Slack Adjuster on [accuridecorp.com](http://accuridecorp.com).

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS

For more information: (800) 823-8332 | [accuridecorp.com](http://accuridecorp.com)

Accuride | 38777 Six Mile Road, Suite 410 | Livonia, MI 48152 USA



**ACCURIDE**  
WHEEL END SOLUTIONS

