

Gunite & KIC Popular Brake Drums

APPLICATION DATA

Brake Size	Gunite/KIC Brand Part Number	GAWR	Weight	Category	Application	Notes
15.00 x 4.00	3721A®X 54201-108	14K 13.2K	79 84	First Fit OEM	Front	Outboard mounted, SAE FF, 5.06 offset, 1.25" dia holes BSM, all axle applications except Mack axles
	G1201X	14K	79	Value		
15.00 x 4.00	3721X 53075-018	14K 14k	79 79	First Fit OEM	Front	Outboard mounted, SAE FF, 5.06 offset, 1.00" dia holes HPM, all axle applications except Mack axles
15.00 x 4.00	3800®X 54293-018	14K 13.2K	79 79	First Fit OEM	Front	Outboard mounted, SAE FF, 5.44 offset, 54293-018 is for HPM only
	G1213X	14K	79	Value		
15.00 x 5.0/6.0	3753X 54295-018	12K 12K	94 79	First Fit OEM	Front	Outboard mounted, SAE FF, 5.44 offset
16.50 x 5.00	3710X 54238-018	14.6K 14.6K	96 84	First Fit OEM	Front	Outboard mounted, SAE FF, 5.06 offset
	80005-018	13.2K	73	Lightweight Trident®		
16.50 x 5.00	3598BX	14.6K	96	First Fit OEM	Front	Outboard mounted, Mack FAW536 axle only, 5.30 offset, 1.00" dia holes HPM
16.50 x 5.00	3758DX	14.6K	96	First Fit OEM	Front	Outboard mounted, SAE FF, 5.44 offset, 1.25" dia holes BSM
16.50 x 6.00	3687X 54242-018	23K 23K	108 126	First Fit OEM	Front	Outboard mounted, SAE FF, 5.06 offset, SAE FL 4.29 offset, 1.25" dia holes BSM
16.50 x 6.00	3772X	23K	107	First Fit OEM	Front	Outboard mounted, SAE FF, Volvo application
16.50 x 7.00	3796X	23K	113	First Fit OEM	Front	Outboard mounted, SAE FL
12.25 x 7.50	3887X 54244-01	17.5K 17.5K	82 89	First Fit OEM	Trailer	Outboard mounted, SAE N, 275mm BC
16.50 x 7.00	3699X 52878-108	23K 23K	128 105	First Fit OEM	Rear	Outboard mounted, SAE R, 8.53 drum pilot, International application
16.50 x 7.00	3600A®X 60001-018	26K 26K	112 108	First Fit OEM	Rear/Trailer	Outboard mounted, SAE R, SAE N & SAE P
	3922X/3922X-018 60000-018	24K 24K	105 102	Value		
	80002-018	23K	88	Lightweight Trident®		
	3576X 54261-018	33.5K 31K	131 125	Heavy Duty		
16.50 x 7.00	3757X 54213-018	21K 21K	114 114	First Fit OEM	Rear	Outboard mounted, International 190 axle
16.50 x 8.00	3782X 54268-018	26k 26k	123 122	First Fit OEM	Rear/Trailer	Outboard mounted, SAE R, SAE N & SAE P
16.50 x 8.62	3807X/3807AX 54229-018	26k 26k	118 117	First Fit OEM	Rear/Trailer	Outboard mounted, SAE R, SAE N & SAE P
	80008-018	20K	102	Lightweight Trident®		
	3811X	33.5K	157	Heavy Duty		

Always make sure to confirm that the Gross Axle Weight Rating (GAWR) for the drum meets or exceeds the maximum axle application rating when recommending an alternative drum part number option^(a).

Value = Value/Low cost option. Value priced option for cost conscious customers.

First Fit OEM = OEM first-fit performance and quality. Customer that wants best performance and lowest overall life cycle costs.

Trident® = Lightweight composite steel shell. Direct interchange with Meritor X30™ and Opti-Lite and Hendrickson/MW CentriFuse® drums.

Heavy Duty = Severe service or heavy duty applications where a higher GAWR is required.

(a) When utilizing KIC Trident lightweight brake drums in lieu of standard brake drums, it may be necessary to replace the disc wheel bolts in order to achieve the proper stud standout due to the difference in the mounting flange thickness.

Your only single source for industry-leading wheel end solutions.

STEEL & ALUMINUM WHEELS | DRUMS | HUBS | ROTORS | SLACK ADJUSTERS

For more information or to place an order: (812) 962-5000 | accuridecorp.com

Gunite | 302 Peoples Avenue | Rockford, IL 61104 USA

WE1.025 0923 ©2023 Accuride Corporation

