

PROSHIELD The Future of Wheel Protection Starts Now

Accuride proudly unveils **ProShield XGT™**—our revolutionary, patent-pending aluminum surface conversion process. Engineered for extreme durability, easy cleanability, and next-level corrosion resistance. The ultimate evolution in wheel protection.

Built to Battle the Elements

ProShield XGT™ is your best defense against the relentless assault of filiform corrosion—especially from today's harsh snow and ice chemicals. This cutting-edge technology:

- **Eliminates significant filiform corrosion** on treated aluminum wheels
- **Withstands** harsh road and weather conditions
- **Xtended Gloss Technology:** a factory-like finish for the entire life of the wheel*

Tested. Proven. Trusted.

We didn't just test it—we pushed it to the limit:

- Simulated **8 years** of brutal real-world exposure
- Cycles of extreme **temperature, humidity, and deicing agents**
- **Result:** No significant filiform corrosion. Period.

Triple-Threat Protection

ProShield XGT™ delivers across the board:

- **Mechanical:** Chip-resistant surface
- **Thermal:** Gloss retention up to **400°F**
- **Chemical:** Resists acids, bases, oils, fuels, brake fluid, and road salts

Effortless Shine, Every Time

Thanks to its hydrophobic finish:

- **Repels** water, oil, and grime
- **Cleans easily** with just soap and water—no harsh chemicals required

Ready to Roll in 2026

- Launching **February 2026**
- Initial part numbers: **43644XGT** and **42362XGT**
- Ordering is simple: just add **XGT** to the part number (e.g., 43644XGT)
- Look for the **ProShield XGT™** sticker on the wheel



Part Number	Wheel Size	Finish
43644XGT	22.5 x 8.25	ProShield XGT™
42362XGT	24.5 x 8.25	ProShield XGT™

Out with the Old, In with the XGT

Select **AccuShield™** part numbers will be phased out and replaced with **ProShield XGT™** equivalents.

- 43644SPC/XPC replaced by 43644XGT
- 42362SPC/XPC replaced by 42362XGT

For more details on ProShield XGT™ and part number transitions, please contact your Accuride sales representative.

*When maintained per Accuride's Cleaning, Handling and Repair Procedures guidelines (ACC2.025)